

??????? :: ??????
 ??? ?????? :: DCCI
 ??? ???????? :: 10
 ?????: 0.18kg
 ??????34.00mm x 50.50mm x 137.00mm

?????: 0.00EGP

????? ???????

Access Control	
Credential Support	BLE and RFID Card
Ingress Protection	IP65
Card	HID iCLASS, HID Prox (COSEC PATH DCCI)
Max. Users	50,000
Event Buffer	5,00,000
Wi-Fi	Yes (802.11 b/g/n)
Bluetooth®	Yes
Ethernet	Yes (10/100Mbps)
PoE	Yes (IEEE 802.3 af)
RS-232	Yes
RS-485	Yes
Wiegand	Wiegand IN/OUT Available
Exit Switch Port	Yes
Door Status Sense	Yes (2 States)
Door Lock Relay	30V DC @ 1 A, Form C, SPDT Relay
Door Lock Power	Internal 12 VDC @ 0.5A or External
Aux-In	No
Aux-Out	No
Reader Interface Types	RS-232 and Wiegand
CPU	Cortex A8 800 MHz
Memory	512 MB Flash + 512 MB DDR3 RAM
LED	Single Tri- Color LED
Buzzer	Yes
Operating Temperature	0°C to +45°C (32°F to 113°F)
Humidity	5% to 95% RH Non - Condensing
Tamper Detection	Yes
Power	12V DC @ 2A

Power to Door Lock	12V DC @ 0.5A (Power to Lock from PATH device) 30V DC @1 A (Power to lock from External power source)
System Integration	API for Software Integration
Operational Modes	Direct Door with COSEC CENTRA Server Panel Door with COSEC PANEL200P
Wall Mount	Yes
Power Adapter	12VDC @ 2A
Battery Backup	Yes (External- 6hrs of Battery Backup on COSEC PATH BBU & COSEC PATH PSBB)

????? ????????