



??????? :: ??????
 ??? ?????? :: ARGO FOM212
 ??? ???? :: 10
 ?????: 0.55kg
 ?????50.00mm x 74.00mm x 186.00mm

?????: 0.00EGP

????? ????????

Access Control	
Credential Support	Bluetooth® (BLE), Fingerprint, RFID Card, PIN, Face (with Compatible Hardware)
Ingress Protection	IP65
Card	MIFARE Classic®, DESFire EV1 and EV2(Read/Write), NFC Tag
Max. Users	50,000
Event Buffer	500,000
Wi-Fi	Yes (802.11 b/g/n)
Bluetooth®	Built-in Bluetooth® (8m Range – For Mobile Applications)
Ethernet	Yes (10/100 Mbps)
PoE	Yes (IEEE 802.3 af)
RS-232	Yes
Wiegand	Wiegand IN/OUT Available
Exit Switch Port	Yes
Door Status Sense	Programmable NO, NC, Supervised
Door Lock Relay	30V DC @ 2 A, Form C, DPDT Relay
Door Lock Power	12V DC @ 0.5A (Power to external Lock from Device) 30V DC @2 A (Power to lock from External power source)
Aux-In	No
Aux-Out	No
Reader Interface Types	RS-232 and Wiegand IN/OUT
CPU	800 MHz ARM Cortex A8 based Processor
Memory	512 MB Flash + 512 MB DDR3 RAM

Buzzer	Yes
Operating Temperature	0°C to +50°C (32°F to 122°F)
Humidity	5% to 95% RH Non-Condensing
Tamper Detection	Yes
Power	12V DC @ 2A
Power to Door Lock	12V DC @ 0.5A (Power to external Lock from Device)
System Integration	API for Software Integration
Operational Modes	Direct Door with COSEC CENTRA / COSEC VYOM Panel Door with COSEC PANEL200P
Wall Mount	Yes – Plastic Back Cover with Screws
???	3.5" IPS Display with Capacitive Touch Panel with Gorilla Glass
??? ?????	320 x 480 Pixel
????? ?????????	IK07
????????? ???????	Yes – Metal Bracket with Screws

????? ?????????

