



??????? ::  
 ??? ?????? :: EZConvert MB705M2P-B  
 ??? ???? :: 10  
 ?????: 67.00g  
 ?????? 70.00mm x 9.50mm x 101.00mm  
 ??? ????:

## ????? ???????

| ICY DOCK Specification          |                                                                                              |
|---------------------------------|----------------------------------------------------------------------------------------------|
| Model Number                    | MB705M2P-B                                                                                   |
| Color                           | Black                                                                                        |
| Support Drive Size              | 1 x M / B + M key M.2 PCIe NVMe SSD<br>2230/2242/2260/2280                                   |
| Compatible Drive Type           | M.2 PCIe 3.0/4.0 NVMe SSD                                                                    |
| Number of M.2                   | 1                                                                                            |
| Host Interface                  | 1 x U.2 SFF-8639, pin-out defined by SFF-9402<br>Rev 1.1 (Tri-mode HBA/RAID card compatible) |
| Transfer Rate                   | Up to 64Gbps                                                                                 |
| Support HDD Capacity            | No limitation                                                                                |
| Structure / Material            | Aluminum & ABS plastic                                                                       |
| Support Hot-Swap                | Yes                                                                                          |
| Package Contents                | Device, mounting screws, user manual, thermal<br>pads                                        |
| U.2 Connector Insertion<br>Rate | 10,000                                                                                       |
| Humidity                        | 5%~65% RH                                                                                    |
| Operating Temperature           | 0°C to 60°C (32°F to 140°F)                                                                  |

## ????? ????????

