



??????? :: ??? ?? ??? ??

??? ?????? :: TS-473A

???? ???????? :: 10

?????: 5.54kg

???????180.20mm x 199.30mm x 279.60mm

?????: 53,000.00EGP

????? ????????

????? ????????????	AMD Ryzen™ Embedded V1500B 4-core/8-thread 2.2 GHz processor
????? ??? ???? ???????????	64-bit x86
????? ????????	?? (AES-NI)
?????????	8 GB SODIMM DDR4 (1 x 8 GB)
??? ?????? ??????????	4
??? ?????????? ??????????	3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
????? ??? ???? ?????????	??
????? ????????	System fan: 1 x 120mm CPU fan: 1 x 60mm
????? ?????? ????????/????????	250W, 100-240V AC, 50-60Hz, 3.5A
Total Memory Slots	2 x SODIMM DDR4 Support ECC memory
Maximum Memory Capacity	64 GB (2 x 32 GB)
M.2 Drive Slots	2 x M.2 2280 PCIe Gen3 x1 slots
PCIe Expansion	2 Slot 1: PCIe Gen 3 x4 Slot 2: PCIe Gen 3 x4
Form Factor (RU)	Tower
Graphic Processors	Optional via a PCIe adapter
Floating Point Unit	??
Hardware-accelerated Transcoding	Optional via a PCIe adapter
Flash Memory	5GB (Dual boot OS protection)

SSD Cache Acceleration Support	??
Wake on LAN (WOL)	??
Jumbo Frame	??
USB 3.2 Gen 2 (10Gbps) Port	3 x Type-A USB 3.2 Gen 2 5V/1A 10Gbps 1 x Type-C USB 3.2 Gen 1 5V/1A 5Gbps
HDMI™ Output	Optional via a PCIe adapter
LED Indicators	Status/Power, USB, LAN, Drive 1-4, M.2 SSD 1-2
Buttons	Power, Reset, USB Auto Copy
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Consumption: Disk Standby Mode	19.576
System Warning	Buzzer
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	2000

????? ????????



