

TS-832PXU

??????? :: ??? ?? ?? ??
 ??? ?????? :: TS-832PXU-4G
 ??? ???????? :: 10
 ?????: 10.76kg
 ?????? 88.60mm x 432.00mm x 511.00mm



?????: 61,000.00EGP

????? ????????

????? ????????????	AnnapurnaLabs Alpine AL324 64-bit ARM® Cortex-A57 4-core 1.7GHz processor
????? ??? ???? ???? ???????????	64-bit ARM
????? ????????	?
???????	4 GB UDIMM DDR4 (1 x 4 GB)
??? ?????? ??????????	8
??? ?????????? ??????????	3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
???? ???? ????????? ???????	? (Not supported M.2 SSD)
???? USB ?????? 3.2	4
????? ???????	2 x 70mm, 12VDC
???? ?????? ??????/???????	250W PSU, 100 - 240V
Total Memory Slots	1 x UDIMM DDR4
Maximum Memory Capacity	16 GB (1 x 16 GB)
M.2 Drive Slots	Optional via a PCIe adapter
PCIe Expansion	1 Slot 1: PCIe Gen 2 x2 PCIe bandwidth limitations will restrict the NAS 10GbE performance. Card dimensions for PCIe slot?220 x

	68.9x 18.76 mm / 8.67 x 2.71 x 0.74 inches.
Form Factor (RU)	2U Rackmount
Floating Point Unit	?
Flash Memory	512 MB (Dual boot OS protection)
Wake on LAN (WOL)	? Only the 2.5GbE port
Jumbo Frame	?
LED Indicators	HDD 1-8, Status, LAN, Storage expansion
Buttons	Power, Reset
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
System Warning	Buzzer
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	700

????? ????????



