



?????: 25,000.00EGP

????? ???????

Processor	ARM 4-core Cortex-A55 2.0GHz processor
Cache	64-bit ARM
Memory	
Storage	?
RAM	4 GB on board (non-expandable) Note: Reserves some RAM for use as shared graphics memory.
Ports	4
Drives	3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Networking	?
USB	1
Power	1 x 120mm, 12VDC
Adapter	Minimum 65W adapter (12VDC), 100-240VAC
Maximum Memory Capacity	4 GB on board (non-expandable)
Form Factor (RU)	Tower
Graphic Processors	Mali-G52
Floating Point Unit	?
Hardware-accelerated Transcoding	?
Flash Memory	4 GB (Dual boot OS protection)
Wake on LAN (WOL)	?
Jumbo Frame	?

LED Indicators	System Status, LAN, USB, HDD1~4
Buttons	Power, Reset, USB Copy
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Consumption: Disk Standby Mode	8.45
System Warning	Buzzer
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	200
Kensington Security Slot	?

????? ????????



