

TSW200



??????? :: ????????

??? ?????? :: TSW200

???? ?????? :: 10

?????: 0.00kg

???????0.00cm x 0.00cm x 0.00cm

?????: 7,500.00EGP

????? ???????

??? ???????	
Industrial switch	
Profinet	Profinet Class A conformance (available with optional order code)
ETH	8 x ETH ports, 10/100/1000 Mbps, supports auto MDI/MDIX crossover
Fibre	2 x SFP ports
IEEE 802.3 series standards	802.3i, 802.3u, 802.3ab, 802.3x, 802.3az
PoE+ ports	Port 1 - 8
PoE standards	IEEE 802.3af (PoE, Type 1) and IEEE 802.3at (PoE+, Type 2), Alternative A (From batch 42) IEEE 802.3af (PoE, Type 1) and IEEE 802.3at (PoE+, Type 2), Alternative B (From batch 1-41)
PoE Max Power per Port (at PSE)	30 W
Total PoE Power Budget (at PSE)	240 W
Operating temperature	-40 °C to 75 °C
Operating humidity	5% to 95% non-condensing
Ingress Protection Rating	IP30
Bandwidth (Non-blocking)	20 Gbps
Jumbo frame support	9216 bytes

MAC address table size	2K entries
------------------------	------------

????? ????????

