## DiskStation DS723+



**Brand:** Synology

**Product Code:** DS723+

**Availability:** 10 **Weight:** 1.51kg

**Dimensions:** 223.00mm x 106.00mm x

166.00mm

Price: 40,659.00EGP

**Short Description**Synology 2 Bay DiskStation DS723+

#### **Description**

## Take your data management to the next level

Versatile smart storage that helps you consolidate and store your growing digital data.



Powerful functionality in a tiny package, with room for 10GbE and dual NVMe drives.



#### Consolidate and share

Flexibly store and organize 40 TB of data, then share with anyone.



## Keep your data safe

Hardware and software engineered to protect your data — trusted by millions.

## Simply faster

DS723+ can handle more demanding application workloads and a greater number of concurrent users compared to prior-generation systems. Experience faster file indexing in Synology Drive, photo organization in Photos, and concurrent file transfers. 

1

Synology Drive 24% faster file indexing

Synology Photos 25% faster photo indexing

Multiple file transfers 32% faster random write

## The performance you need

Reduce transfer times with the DS723+, designed to accelerate your workloads. Easily add faster networking and NVMe drives to further boost performance.

Up to 471/225 MB/sread/write

Up to 10GbEnetworking

 $2 \times M.2NVMecache \& storage pool$ 

## Versatile and flexible storage

Make the most of high-performance networking and file access without taking up unnecessary space. DS723+ comes equipped with 2 bays and can scale up to 7 bays with the DX517 expansion unit as your data needs grow.

2 bays20TB

-

7 bays100 TB

## Store, share, and protect

Manage all your documents, photos, and other files, back up applications and devices, and protect your assets with professional video surveillance.





## Multi-layered backup



Smart surveillance

## **Private cloud storage**

Access files from all your devices and protect them with smart versioning. Manage, share, and sync your data across locations.

Consolidate data management

Collaborate across sites

#### A private cloud for all your devices

Effortlessly deploy your own personal cloud with Synology's private cloud solution. Simplify file access and consolidate your data management to benefit from easier file sharing and collaboration.

#### **Professional photo management**

Efficiently back up and organize photos and videos with management tools for novice and professional users alike. Automatically organize your content into albums and create secure share links to share files with family, friends, or clients.

## Sync files and folders between sites

Site-to-site file syncing allows collaborators to sync individual files or folders between Synology devices, whether at home, another office, or across the world. Combine convenient access with 100% data ownership.

Share data with the power of the cloud

Reduce your on-site storage footprint and benefit from data center network speeds with hybrid cloud technology. Set up Hybrid Share Folders to efficiently store cold data in the cloud, while keeping frequently accessed files cached locally on your DS723+ and accessible at LAN speeds.



#### Multi-layered backup

Back up files, folders, physical devices, VMs, and SaaS applications with free solutions, and protect your NAS with built-in technologies.

Back up all your devices

Protect your Synology system

### Centralize your backup and recovery solution

Consolidate and automate backup tasks for PCs, file servers, VMs, SaaS applications, and more with Active Backup Suite. Administer device backups remotely through a centralized portal and quickly restore specific files or entire devices to keep your business up and running. Take advantage of built-in remote backup solutions designed to protect your data with seamless 3-2-1 backup configurations.

#### Perform full Synology system backups

Protect all data, applications, and configurations on your Synology systems with comprehensive scheduled backups to local and remote servers, external drives, or cloud storage destinations including Synology C2 Storage.

### Protect folders and LUNs with snapshots

Configure efficient point-in-time snapshots of shared folders and LUNs at intervals as short as 5 minutes. Allow users to easily restore previous versions of files unassisted, quickly recover VMs, and copy snapshots to another server to benefit from rapid storage failover.

Smart surveillance
Γransform your Synology device into a full-featured video management system for a wide range of compatible IP cameras.
Monitor and protect your business
Back up your surveillance footage

## **Synology Surveillance Station**

Protecting your business has never been easier with centralized video management, support for over 8,300 IP camera models, and remote monitoring and playback of footage. Synology's surveillance management system provides all the tools you need for live monitoring, alerts, investigation, management, and backup.



#### **Software**

**DSM Specifications** 

Storage Management Maximum Single Volume 108 TB

Size

Maximum Internal Volume 64

Number

M.2 SSD Storage Pool

Support\*

SSD Read/Write Cache

(Determining cache size)

SSD TRIM

Supported RAID Type

• Synology Hybrid

**RAID** • Basic • JBOD • RAID 0 • RAID 1 • RAID 5 (with **Expansion Unit)** • RAID 6 (with **Expansion Unit)** • RAID 10 (with **Expansion Unit) RAID Migration** • Basic to RAID 1 • Basic to RAID 5 (with Expansion Unit) • RAID 1 to RAID 5 (with Expansion Unit) • RAID 5 to RAID 6 (with Expansion Unit) • Synology Hybrid Volume Expansion with Larger HDDs **RAID** • RAID 1 • RAID 5 (with **Expansion Unit**) • RAID 6 (with **Expansion Unit)** • RAID 10 (with **Expansion Unit)** • Synology Hybrid Volume Expansion by Adding a HDD **RAID** • JBOD (with **Expansion Unit)** • RAID 5 (with **Expansion Unit)** 

• RAID 6 (with

RAID (with

• RAID 1 (with

• RAID 5 (with

Expansion Unit)Synology Hybrid

**Expansion Unit**)

Expansion Unit)

**Expansion Unit)** 

Global Hot Spare Supported RAID Type

Notes

- RAID 6 (with Expansion Unit)
- RAID 10 (with Expansion Unit)
- Creating M.2 storage pools requires the use of Synology-verified SSDs, which are rigorously tested under extreme temperature conditions. Thermal parameters for SSDs and NAS units are fine-tuned to ensure optimal management of thermal conditions under I/O-intensive environments. (Learn more)
- Usable capacity for each volume will be lower than the maximum volume size and is dependent on the filesystem and the amount of system metadata stored.
- Actual maximum storage pool and volume sizes vary depending on drives used, the number of drive bays available, and the RAID configuration.
- Each internal volume (may consist of multiple drives) is expandable up to 108TB.
- Btrfs

**External Drives** 

File Protocol

- ext4
- Btrfs
- ext4
- ext3
- FAT
- NTFS
- HFS+
- exFAT
- CXIAI
- SMBAFP
- AIT
- NFSFTP
- WebDAV
- Rsync

Maximum Concurrent 500

SMB/AFP/FTP Connections

Maximum Concurrent 2,000

SMB/AFP/FTP Connections

(with RAM expansion)

Windows Access Control

List (ACL) Integration

NFS Kerberos Authentication

Notes

- Regarding data concerning tests with RAM expansion, all memory slots are installed with the maximum capacity of supported RAM.
- The testing standard was based on the maximum number of concurrent connections supported by this model. During the testing, 25% of the connections were used to transfer files concurrently. The transfer process guaranteed that the connections were not

File Services

interrupted; the minimum transfer speed was not guaranteed.

Account & Shared Folder Maximum Local User 2,048

Accounts

Maximum Local Groups 256 Maximum Shared Folder 512 Maximum Shared Folder 8

Sync Tasks

Hybrid ShareHybrid Share Folder Number 10Hyper BackupFolder and Package Backup

**Entire System Backup** 

Notes Full-system backup requires

DSM 7.2 or later.

<u>High Availability</u> Synology High Availability

Log CenterSyslog Events per Second800VirtualizationVMware ESXi 6.5 and VAAI

Windows Server 2022

Citrix Ready OpenStack

General Specifications Supported Protocols SMB1 (CIFS), SMB2,

SMB3, NFSv3, NFSv4, NFSv4.1, NFS Kerberized sessions, iSCSI, HTTP,

HTTPs, FTP, SNMP, LDAP,

**CalDAV** 

Supported Browsers • Chrome

FirefoxEdgeSafari

Supported Language English, Deutsch, Français,

Italiano, Español, Dansk, Norsk, Svenska, Nederlands, ??????, Polski, Magyar,

Português do Brasil,

Português Europeu, Türkçe, ?eský, ???????, ???, ???,

????, ????

Notes For an updated list of

supported browser versions, check the <u>DSM Technical</u>

		Specifications.
Add-on Packages view the c	complete package list	
Central Management System	<u>n</u>	
Synology Chat	Suggested Users Notes	<ul> <li>Measured with simulated users, each with an average record of 20,000 messages, emojis, or stickers. The required server response time is below ten seconds.</li> <li>Models with expandable memory are tested with their maximum supported memory.</li> </ul>
Download Station	Maximum Concurrent Download Tasks	80
SAN Manager	Maximum iSCSI Target Number	128
	Maximum LUN LUN Clone/Snapshot, Windows ODX	256
Synology MailPlus / MailPlus Server	Free Email Accounts	5 (Additional accounts require purchase of licenses)
	Suggested Users	500
	Maximum Server	1,224,000 emails per day,
	Performance	approx. 37GB
	Notes	<ul> <li>Suggested users is derived from testing</li> </ul>
		in an environment
		with 20% heavy users (each with 20,000 pre-
		1 , 1 , 1

<u>Learn more</u>Models with 2 bays

populated emails and receiving 240 emails

receiving an average of 20 emails per day).

per day) and 80% light users (each

and dual M.2 drive slots were installed with two SSDs for SSD cache.

- Models with expandable memory are tested with their maximum supported memory.
- The performance of the mail system will slightly decrease in high-availability mode due to data synchronization between the two servers.
- Functions that were enabled in all of the tests above: antispam, anti-virus, DNSBL, greylist, content scan, full-text search (English only).

<u>Media Server</u>	DLNA Compliance
Synology Photos	Facial Recognition
	Object Recognition

Notes

Object recognition requires an upgrade of memory capacity to a minimum of 4 GB.

1,024

65,536

Maximum Snapshots per **Snapshot Replication** 

Shared Folder

Maximum of System

**Snapshots** 

**Default Licenses** 

2 (Additional cameras require purchase of licenses)

• 720p: 40 channels, 1200 FPS

• 1080p: 40 channels, 800 FPS

• 3M: 35 channels, 350

Suggested Maximum IP Cameras and Total FPS

(H.264)

Surveillance Station

Suggested Maximum IP Cameras and Total FPS (H.265)

**Notes** 

- **FPS**
- 5M: 28 channels, 280 FPS
- 4K: 17 channels, 170 FPS
- 720p: 40 channels, 1200 FPS
- 1080p: 40 channels, 1200 FPS
- 3M: 40 channels, 600 FPS
- 5M: 40 channels, 480 FPS
- 4K: 20 channels, 200 FPS
- Performance figures are obtained from testing conducted with the device fully populated with drives, with their default memory configuration, and under a continuous recording setup. Actual system capabilities may vary based on configuration, drive performance, enabled features, and the presence of additional workloads.
- Use <u>NVR Selector</u> to quickly find a suitable model based on your requirements.
- The maximum number of camera stream outputs is 2 times the suggested maximum number of

Synology Drive

Recommended Number of Concurrent Sync Clients

IP cameras. 350 (the number of connections that can be maintained when the recommended number of hosted files was reached) 5,000,000 (applies to files indexed or hosted by Synology Drive. For file access through other standard protocols, refer to the File

Recommended Number of **Hosted Files** 

Services section above)

**Notes** 

- Exceeding the recommended numbers above will not block application operations, but may result in longer response time.
- Utilizing SSD cache can significantly improve performance.
- Models with expandable memory are tested with their maximum supported memory.
- Btrfs file system and non-encrypted shared folders were used during the aforementioned testing.

**Synology Office** 

Suggested Users Notes

3,000

 Suggested users is derived from testing in an environment with 60% idle users (each logging in and viewing documents) and 40% active users (each executing

random actions at intervals of 20 to 40 seconds) operating within documents, each document having 30 users. Learn more

- Models with expandable memory are tested with their maximum supported memory.
- Client performance may affect maximum simultaneous editing users. Client PCs used for testing: Intel Core i3-3220 / 8GB RAM

<u>Virtual Machine Manager</u> Recommended Virtual 4 (<u>Learn more</u>)

**Machine Instances** 

Recommended Virtual DSM 4 (including 1 Free License)

Number (Licenses required)

Notes The specifications vary

depending on system

configuration and memory

size.

<u>VPN Server</u> Maximum Connections 40

**Specification** 

NAS	
CPU Model	AMD Ryzen R1600
CPU Quantity	1
CPU Core	2
CPU Architecture	64-bit
CPU Frequency	2.6 (base) / 3.1 (turbo) GHz
Hardware Encryption	YES
Engine	
Memory	2 GB DDR4 ECC SODIMM
Drive Bays	2
Compatible Drive Type	3.5
Compatible Drive Type	3.5
Hot Swappable Drive	YES
RJ-45 1GbE LAN Port	2

USB 3.2 Gen 1 Port	1
System Fan	92 mm x 92 mm x 1 pcs
Power Supply Unit / Adapter	65 watts 100V to 240V AC 50/60 Hz, Single Phase
Total Memory Slots	2
Maximum Memory Capacity	32 GB (16 GB x 2)
M.2 Drive Slots	2 (NVMe)
<b>Expansion Port</b>	1
PCIe Expansion	1 x Gen3 x2 network upgrade slot

# **Product Gallery**





