



??????? :: ??????  
 ??? ?????? :: DCCE  
 ???? ???????? :: 10  
 ??????: 0.15kg  
 ????????33.00mm x 50.00mm x 136.00mm  
 ???? ??????:

????? ????????

Access Control	
Bluetooth®	Yes
Buzzer	Yes
Buzzer	Yes
Card	EM Proximity Card
CPU	800 MHz ARM Cortex A8 based Processor
Credential Support	Bluetooth® (BLE) and RFID Card
Door Lock Power	12V DC @ 0.5A (Power to External Lock from Device) 30V DC @ 1A (Power to Lock from External power source)
Door Lock Relay	Yes
Door Status Sense	Yes(2State)
Ethernet	Yes (10/100 Mbps)
Event Buffer	500,000
Exit Switch Port	Yes
Humidity	5% to 95% RH Non-Condensing
Ingress Protection	IP65
LED	Yes
Max. Users	50,000
Memory	512 MB Flash + 512 MB DDR3 RAM
Operating Temperature	0°C to +50°C (32°F to 122°F)
Operational Modes	Direct Door with COSEC CENTRA / COSEC VYOM Panel Door with COSEC PANEL200P
PoE	Yes (IEEE 802.3 af)
Power	12V DC @ 2A
Power to Door Lock	12V DC @ 0.5A (Power to Lock from Device)

Reader Interface Types	RS-232 and Wiegand
RS-232	Yes
RS-485	Yes
System Integration	API for Software Integration
Tamper Detection	Yes
Wall Mount	Yes
Wi-Fi	Yes
Wiegand	Yes (Selectable IN/OUT) IN: 26 Bit format OUT: Configurable

????? ????????



RFID



BLUETOOTH

Multiple Credentials



WIEGAND



RS-232



DOOR LOCK RELAY



EXIT SWITCH

Multiple Interfaces



IP65

Certification