

COSEC PATH DCCE



Brand: Matrix
Product Code: DCCE
Availability: 10
Weight: 0.15kg
Dimensions: 33.00mm x 50.00mm x 136.00mm
Call for Price:

Short Description

EM Proximity Card Based Compact Door Controller

Description



Multiple User Credentials

RFID Cards

Mobile through BLE

Dual Verification for High-Security Applications



Multiple Connectivity Options

Built-in Bluetooth, Wi-Fi, PoE, Ethernet

Use Existing IT Infrastructures to Meet Future Requirements

Low IT Infrastructure Cost and Future Proof

↓

Higher User and Template Capacity

Stores up to 50,000 User Profiles

Event Log Capacity of 5,00,000

↓

Features



Secured Communication

Secure data transmission with SSL encryption, providing a highly reliable solution that is snoop-proof and hack-proof



Tamper Detection

Provides better security with tamper detection, instantly alerting to any vandalism acts, ensuring enhanced protection for devices



Weather Resistance with IP65

Offers weather resistance with an IP65 rating, providing reliable ingress protection against dust and water, making it ideal for outdoor applications



Superior Design

Features a superior design that not only enhances the product's lifespan but also significantly improves performance, all while providing an appealing aesthetic



Plug and Play

Offers plug and play installation with built-in web software, ensuring fewer touches, simple management, and significantly reduced installation time



Auto Push Event Data

Eliminates the need to download event data individually, saving valuable time for admin and ensuring an accurate employee attendance process at all times

Specification

Access Control	
Bluetooth®	Yes
Buzzer	Yes
Buzzer	Yes

Card	EM Proximity Card
CPU	800 MHz ARM Cortex A8 based Processor
Credential Support	Bluetooth® (BLE) and RFID Card
Door Lock Power	12V DC @ 0.5A (Power to External Lock from Device) 30V DC @ 1A (Power to Lock from External power source)
Door Lock Relay	Yes
Door Status Sense	Yes(2State)
Ethernet	Yes (10/100 Mbps)
Event Buffer	500,000
Exit Switch Port	Yes
Humidity	5% to 95% RH Non-Condensing
Ingress Protection	IP65
LED	Yes
Max. Users	50,000
Memory	512 MB Flash + 512 MB DDR3 RAM
Operating Temperature	0°C to +50°C (32°F to 122°F)
Operational Modes	Direct Door with COSEC CENTRA / COSEC VYOM Panel Door with COSEC PANEL200P
PoE	Yes (IEEE 802.3 af)
Power	12V DC @ 2A
Power to Door Lock	12V DC @ 0.5A (Power to Lock from Device)
Reader Interface Types	RS-232 and Wiegand
RS-232	Yes
RS-485	Yes
System Integration	API for Software Integration
Tamper Detection	Yes
Wall Mount	Yes
Wi-Fi	Yes
Wiegand	Yes (Selectable IN/OUT) IN: 26 Bit format OUT: Configurable

Product Gallery



RFID



BLUETOOTH

Multiple Credentials



WIEGAND



RS-232



DOOR LOCK
RELAY



EXIT
SWITCH

Multiple Interfaces



Certification