

DiskStation DS224+



Brand: Synology

Product Code: DS224+

Availability: 10

Weight: 1.30kg

Dimensions: 232.20mm x 108.00mm x
165.00mm

Price: 29,155.00EGP

Short Description

Synology 2 Bay DiskStation DS224+

Description

Keep your data on-site



Consolidate and safeguard

Protect all your data with integrated security features and centralized access.



Manage important data

Share, back up, and access files, photos, surveillance video, and more.



Minimize energy impact

15 watts under full operation keeps operating costs low.

Simply faster

DS224+ is faster at indexing files in Synology Drive and Synology Photos and more capable of running demanding web applications compared to previous-generation systems.

Web applications 62% more responses per second

Synology Drive 52% faster file indexing

Synology Photos 28% faster image indexing

Store, share, and protect

Manage all your documents, images, and other files, back up applications and devices, and protect your property with professional video surveillance.

Private cloud for data sharing

Hybrid work in the private cloud

Store, sync, access, and share data from any device, wherever you are. Work together seamlessly across different platforms, accessing files through mobile apps, desktop clients, or a browser-based interface. Quickly and easily roll back files in case of unwanted deletion or modification thanks to smart versioning.

Keep your photos organized

Synchronize data between sites

Manage data with the power of the cloud



Multi-layered backup

Back up workstations, smartphones, cloud apps, and more

Consolidate and automate backup tasks for workstations, file servers, VMs, SaaS applications, and more with Active Backup Suite. Administer device backups remotely through a centralized portal and quickly restore specific files or entire devices to keep

your business up and running. Take advantage of built-in remote backup solutions designed to protect your data with seamless 3-2-1 backup configurations.

Perform full Synology system backups

Protect folders and LUNs with snapshots



Smart surveillance management

Synology Surveillance Station

Protecting your business has never been easier, with centralized management, support for over 8,300 IP camera models, and remote monitoring and playback. Synology's video management system provides all the tools you need for live monitoring, investigation, management, and backup.

Dual recording to the cloud



Btrfs: advanced file system for data protection

The Synology DiskStation Manager (DSM) operating system that powers the DS224+ uses the advanced Btrfs file system, which safeguards your data against corruption and allows for the reversal of unintended or malicious changes through the use of snapshot technology.



Software

DSM Specifications

[Storage Management](#)

Maximum Single Volume Size	108 TB
Maximum Internal Volume Number	64
SSD TRIM	
Supported RAID Type	<ul style="list-style-type: none">• Synology Hybrid RAID• Basic• JBOD• RAID 0• RAID 1• Basic to RAID 1• Synology Hybrid RAID• RAID 1• Synology Hybrid RAID• Usable capacity for each volume will be lower than the maximum volume
RAID Migration	
Volume Expansion with Larger HDDs	
Volume Expansion by Adding a HDD	
Notes	

size and is dependent on the filesystem and the amount of system metadata stored.

- Actual maximum storage pool and volume sizes depend on drive sizes used, the number of drive bays available, and the RAID configuration.

[File System](#)

Internal Drives

External Drives

- Btrfs
- ext4
- Btrfs
- ext4
- ext3
- FAT
- NTFS
- HFS+
- exFAT
- SMB
- AFP
- NFS
- FTP
- WebDAV
- Rsync

[File Services](#)

File Protocol

Maximum Concurrent 500

SMB/AFP/FTP Connections

Maximum Concurrent 1,500

SMB/AFP/FTP Connections

(with RAM expansion)

Windows Access Control

List (ACL) Integration

NFS Kerberos Authentication

Notes

- Regarding data concerning tests with RAM expansion, all memory slots are installed with the maximum capacity of supported RAM.

- The testing standard was based on the maximum number of concurrent connections supported by this model. During the testing, 25% of the connections were used to transfer files concurrently. The transfer process guaranteed that the connections were not interrupted; the minimum transfer speed was not guaranteed.

Account & Shared Folder	Maximum Local User Accounts	2,048
	Maximum Local Groups	256
	Maximum Shared Folder	256
	Maximum Shared Folder Sync Tasks	8
	Maximum Hybrid Share Folders	10
Hybrid Share	Folder and Package Backup	
Hyper Backup	Entire System Backup	
	Notes	Full-system backup requires DSM 7.2 or later.
High Availability	Synology High Availability	
Log Center	Syslog Events per Second	800
General Specifications	Supported Protocols	SMB1 (CIFS), SMB2, SMB3, NFSv3, NFSv4, NFSv4.1, NFS Kerberized sessions, iSCSI, HTTP, HTTPS, FTP, SNMP, LDAP, CalDAV
	Supported Browsers	<ul style="list-style-type: none"> • Chrome • Firefox • Edge • Safari
	Supported Language	English, Deutsch, Français,

Italiano, Español, Dansk, Norsk, Svenska, Nederlands, ??????, Polski, Magyar, Português do Brasil, Português Europeu, Türkçe, ?eský, ??????, ???, ???, ???, ????

For an updated list of supported browser versions, check the [DSM Technical Specifications](#).

Notes

Add-on Packages [view the complete package list](#)
[Central Management System](#)
[Synology Chat](#)

Suggested Users
 Notes

100

- Measured with simulated users, each with an average record of 20,000 messages, emojis, or stickers. The required server response time is below ten seconds.
- Models with expandable memory are tested with their maximum supported memory.

Download Station

Maximum Concurrent
 Download Tasks

80

[SAN Manager](#)

Maximum iSCSI Target
 Number

128

Maximum LUN
 LUN Clone/Snapshot,
 Windows ODX

256

[Synology MailPlus /
 MailPlus Server](#)

Free Email Accounts

5 ([Additional accounts
 require purchase of licenses](#))

Suggested Users
 Maximum Server
 Performance
 Notes

500

1,224,000 emails per day,
 approx. 37GB

- Suggested users is derived from testing in an environment

with 20% heavy users (each with 20,000 pre-populated emails and receiving 240 emails per day) and 80% light users (each receiving an average of 20 emails per day). [Learn more](#)

- Models with expandable memory are tested with their maximum supported memory.
- The performance of the mail system will slightly decrease in high-availability mode due to data synchronization between the two servers.
- Functions that were enabled in all of the tests above: anti-spam, anti-virus, DNSBL, greylist, content scan, full-text search (English only).

[Media Server](#) [Synology Photos](#)

DLNA Compliance
Facial Recognition
Object Recognition
Notes

Object recognition requires an upgrade of memory capacity to a minimum of 4 GB.

[Snapshot Replication](#)

Maximum Snapshots per Shared Folder
Maximum of System Snapshots

1,024

65,536

[Surveillance Station](#)

Default Licenses

2 ([Additional cameras require purchase of licenses](#))

Suggested Maximum IP
Cameras and Total FPS
(H.264)

- 720p: 25 channels, 750 FPS
- 1080p: 25 channels, 750 FPS
- 3M: 25 channels, 350 FPS
- 5M: 25 channels, 280 FPS
- 4K: 17 channels, 170 FPS

Suggested Maximum IP
Cameras and Total FPS
(H.265)

- 720p: 25 channels, 750 FPS
- 1080p: 25 channels, 750 FPS
- 3M: 25 channels, 600 FPS
- 5M: 25 channels, 480 FPS
- 4K: 20 channels, 200 FPS

Notes

- Performance figures are obtained from testing conducted with the device fully populated with drives, with their default memory configuration, and under a continuous recording setup. Actual system capabilities may vary based on configuration, drive performance, enabled features, and the presence of additional workloads.
- Use [NVR Selector](#) to quickly find a suitable model based on your requirements.

[Synology Drive](#)

Recommended Number of Concurrent Sync Clients	350 (the number of connections that can be maintained when the recommended number of hosted files was reached)
Recommended Number of Hosted Files	5,000,000 (applies to files indexed or hosted by Synology Drive . For file access through other standard protocols, refer to the File Services section above)

Notes

- The maximum number of camera stream outputs is 2 times the suggested maximum number of IP cameras.
- Exceeding the recommended numbers above will not block application operations, but may result in longer response time.
- Models with expandable memory are tested with their maximum supported memory.
- Btrfs file system and non-encrypted shared folders were used during the aforementioned testing.

[Synology Office](#)

Suggested Users	1,500
Notes	

- Suggested users is derived from testing in an environment with 60% idle users (each logging in and viewing documents)

and 40% active users (each executing random actions at intervals of 20 to 40 seconds) operating within documents, each document having 30 users. [Learn more](#)

- Models with expandable memory are tested with their maximum supported memory.
- Client performance may affect maximum simultaneous editing users. Client PCs used for testing: Intel Core i3-3220 / 8GB RAM

Virtual Machine Manager	Recommended Virtual Machine Instances	2 (Learn more)
	Recommended Virtual DSM Number (Licenses required)	2 (including 1 Free License)
	Notes	The specifications vary depending on system configuration and memory size.
VPN Server	Maximum Connections	40

Specification

NAS	
CPU Model	Intel Celeron J4125
CPU Quantity	1
CPU Core	4
CPU Architecture	64-bit
CPU Frequency	2.0 (base) / 2.7 (turbo) GHz
Hardware Encryption Engine	YES
Memory	2 GB DDR4 non-ECC
Drive Bays	2
Compatible Drive Type	3.5
Hot Swappable Drive	YES

RJ-45 1GbE LAN Port	2
USB 3.2 Gen 1 Port	2
System Fan	92 mm x 92 mm x 1 pcs
Power Supply Unit / Adapter	60 watts 100V to 240V AC 50/60 Hz, Single Phase
Total Memory Slots	1
Maximum Memory Capacity	18 GB (2 GB + 16 GB)

Product Gallery